



The Fast and Easy Professional Finishing System

The NEW ProSEAL® 44 Pouch Board Laminator is a fast, easy-to-use, and cost-effective finishing systems. Its simple, one-step operation, on-demand capabilities, and minimal maintenance make it ideal for start-up finishing departments, corporate in-house centers, frame shops, service bureaus, photo studios, quick printers, and schools.

A complete product line of rigid and flexible laminating pouches and mounting boards are offered by Seal Graphics. When teamed with the ProSEAL 44, the offering is a complete Pouch Board laminating and mounting solution for quick, easy and low-cost finishing applications.

Add Value

Mounting and laminating add value to posters, prints and photos making them display-ready. The ProSEAL 44 Laminator makes mounting and laminating your graphic materials quick, easy and convenient. And you'll always be assured of consistent, high-quality results with the ProSEAL 44's low profile space-saving design, easy-to-use thickness selector knob with pre-set roller pressure (for substrates up to 1/4" thick), pre-set digitally controlled temperature, a heat on/off control, reverse mode, silicone rollers for minimal maintenance, and a 1-year warranty on parts/90 day warranty on rollers. And you can always feel secure knowing that the ProSEAL Laminator is backed by a name well known and respected worldwide for innovative, superior finishing solutions – SEAL.

FEATURES:

- Low profile space-saving design for convenient fit on work table or cart
- Easy-to-use thickness selector knob
- Pre-set roller pressure
- Single heated roller
- Pre-set digitally controlled heat to ensure consistent temperature
- Heat on/off control
- Reverse mode provides quick misfeed correction
- Silicone rollers and easy-clean features mean minimal maintenance
- 1-year warranty on parts / 90-day warranty on rollers

Technical Specifications

Part Number	63050
Maximum Width	44" (1120 mm)
Maximum Temperature	Up to 320° F (Up to 160° C)
Maximum Speed	1.0 fpm (305 mm/min.)
Maximum Pressure	0.8 N/mm
Electrical	120V / 60Hz / 15A
Thickness Settings	0 (rollers closed) 1/16" (1.5 mm) 1/8" (3 mm) 3/16" (5 mm) 1/4" (6 mm)
Product Dimensions (WxDxH)	55.6" x 20.5" x 12.6" (1412 x 520 x 320 mm)
Net Weight	119 lbs. (54 kg)
Shipping Dimensions (WxDxH)	61.2" x 29.1" x 20.5" (1554 x 740 x 520 mm)
Shipping Weight	165 lbs. (75 kg)
Safety Certifications	ETL listed for US and Canada. Meets UL safety standards.

Seal Graphics Americas Corporation
7091 Troy Hill Drive
Elkridge, MD 21075
Tel: 410-379-5400
Fax: 410-579-8960

Seal Graphics Canada
1601 Matheson Blvd. E.
Mississauga, Ontario
Canada, L4W 1H9
Tel: 905-212-9232
Fax: 905-212-9313



Contact your local distributor

